

INTRODUCTION

- Series of ministep bipolar chopper drives, suitable for driving medium power two-phase stepping motors, with four, six or eight terminals.
- Compact, easy to use and cost effective solution. This system is designed for easy mounting inside a metallic electrical cabinet.
- Target: medium and medium-low power applications without special configuration requirement, but needing great dynamic performance, high reliability, low acoustic noise and mechanic vibrations reduction.

HIGHLIGHTS

- Microstepping function up to 4.000 step/ rev.
- Electronic damping facility for further acoustic noise and mechanic vibrations reduction at low and medium speed.
- Separated connectors for logic signals and power connections.
- Optoinsulated and differential input and output signals ease interfacing with the most commonly used control systems.

| Series | Model | V _{dc} range (Volt) | I _{NP} min. (Peak value) (Amp) | I _{NP} max. (Peak value) (Amp) | Dimensions (mm) |
|--------|------------|---------------------------------|---|---|--------------------|
| NDC | 04 - 04.V* | 24 to 75 | 0.6 | 2.0 | 101x94x25 |
| NDC | 06 - 06.V* | 24 to 75 | 1.9 | 6.0 | 101x94x25 |
| NDC | 94 | 24 to 75 | 0.6 | 2.0 | 110x108x34 |
| NDC | 96 | 24 to 75 | 1.9 | 6.0 | 110x108x34 |

* NDC 04.V and NDC 06.V versions are equipped with screw-type connectors.



Gral. C.M.de Alvear 171
(B1832BVC) - Lomas de Zamora



(+54 11) 3988-7001



Whatsapp
(+54 911) 5383-9778



ventas@varitel.com




TECHNICAL FEATURES

- Range of operating voltages: 24-75 V_{DC}.
- Range of current: 0.6-6.0 Amp. Setting up to eight possible values by means of dip-switches.
- Microstepping: 400, 800, 1.600, 3.200 and 500, 1.000, 2.000, 4.000 steps /revolution. Setting by means of dip-switches.
- Automatic current reduction at motor standstill.
- Protections:
 - Protection against under-voltage and over-voltage.
 - Protection against a short-circuit at motor outputs.
 - Overtemperature protection with thermal sensor.
- Optoinsulated inputs compatible with differential control signals.
- Possibility to switch off motor current with an external logic signal.
- High efficiency CHOPPER with MOSFET final stage output.
- Electronic damping facility for further acoustic noise and mechanic vibrations reduction at low and medium speed.
- Available a version with built-in oscillator, with speed range from 14 to 450 rpm. Setting by means of dip-switches.
- Version: boxed/open frame, equipped with crimp-type or screw-type connectors. Maximum compactness.
- Warranty: 24 months.



POWER AND LOGIC CONNECTIONS



MECHANICAL DIMENSIONS

